





















# MASKING - PLUG SELECTOR GUIDE

Description		Fits Hole Size (mm)		Products
		From	To	
<b>Tapered Plugs</b> Over 50 different sizes		0.79	127.00	UP, MSP, HUP, GN, BN
<b>Tapered Plugs with Handle</b> Handle provides extra grip during installation and removal		0.79	55.96	HUP-H, UP-H
<b>Hollow Cone Plugs</b> Ideal for slotted and oval holes		3.74	55.96	UHCP
<b>Mouse Tail Plugs</b> For very small holes		0.64	2.03	SMT100, MT100
<b>Thread Mask Plugs</b> Masks the first thread of a threaded hole		2.72	22.76	UTM
<b>Flexible Tapered plugs</b> Provides a snug but flexible fit when pushed into open ports		4.95	32.39	HVTP, VTP
<b>Flangeless Plugs</b> Protects the thread of a blind hole		3.99	31.90	UFP, FP
<b>Pull Plugs</b> Masks the length of a through hole		1.57	35.05	PP, SPP
<b>Pipe Thread Mask Plug</b> Masks internally threaded ends of tubing		18.31	83.66	PTM
<b>Hollow Flanged Pull Plugs</b> Protects the chamfer of threaded through holes		5.00	17.15	HFPP
<b>Dual Flanged Pull Plugs</b> Ideal for weld nuts		5.00	16.99	DFPP
<b>Multi Flanged Plugs</b> One size fits a multitude of holes		4.00	18.00	UMFP
<b>Washer Pull Plugs</b> Provides a paint free area around holes		2.67	11.66	UWPP
<b>Tapered Vinyl Plugs</b> Tapered design for plugging small holes		1.78	8.64	HTP, TP
<b>Dual Purpose Washer Plugs</b> Double use, provides paint free area around a hole		2.44	12.70	UW
<b>Hollow Washer Plugs</b> For masking the earthing area around the hole		6.30	22.00	HWP
<b>Flanged Plugs</b> Masks a hole and first thread		7.39	13.69	SFP
<b>Step Plugs</b> Provides paint free area around a hole		3.00	8.23	SP
<b>Double Washer Plugs</b> For masking simultaneously entry/exit threads on weld nuts/press nuts etc		M4	M16	DWP
<b>Self Threading Plugs</b> Self tapping leak proof seal		1.52	11.34	STP
<b>Custom Plugs</b> Material temperatures up to 315°C and designs to suit your application				